

**RBT45 Series**

<b>Features</b>	<b>Benefits</b>
<b>Warranty</b>	One year parts & labor. See warranty page for complete details.
<b>96" &amp; 108" Working widths</b>	Choice of two sizes to pick from. Both sizes handle large capacities.
<b>70-125 hp range</b>	Fits a wide variety of tractors.
<b>Cat. 2 and 3</b>	Bushing provided to go from Cat. 2 to Cat. 3 enables a wider variety of tractors to be used.
<b>Quick hitch compatible</b>	Compatible with Land Pride Quick hitch for easy attachment and removal. Increases productivity.
<b>Blade angles left and right up to 45° in either direction</b>	(15 positions manually: Center, 7 clockwise and 7 counterclockwise) (Hydraulically: Any degree up to 45 degrees) Allows operator to set the blade at the angle of his choice up to 45° to move the desired amount of material with satisfactory results.
<b>Blade offsets left and right up to 35"</b>	(15 positions manually: Center, 7 positions left and 7 positions right) (Hydraulically: Any position up to 35") Allows the operator to position the end of the moldboard beyond tractor tire and close to solid obstacles such as fences, buildings and abutments.
<b>Blade tilts up and down up to 15°</b>	Allows the operator to do simple tasks such as putting a crown in the middle of a road to making V-type ditches of various sizes.
<b>Fully welded reinforced main frame</b>	Overall mainframe strength is enhanced due to being fully welded.
<b>Heavy-duty pivot assembly with 4" solid steel kingpin</b>	1" Plate steel turntable and 4" kingpin for handling the high amount of torque that can be transferred to this area.
<b>Formed 19" moldboard with top lip reinforcement</b>	Formed moldboard with 90 degree bent top for additional strength. Tall moldboard allows for a great deal of material to be moved.
<b>5/16" Moldboard with 1/4" reinforcement</b>	Heavy-duty moldboard to handle loads from 125 hp tractors.
<b>Grease zerks at all pivot points</b>	Helps front pivot shaft maintain bind free movement.
<b>Reversible cutting edge</b>	Lengthens blade life by being able to turn cutting edge over and use other edge.
<b>Retractable parking stand</b>	Enables one person hook-up and keeps the mainframe off of the ground.
<b>Skid shoes (optional)</b>	Skid shoes protect moldboard from hitting low-lying obstructions such as manhole covers.
<b>End plates (optional)</b>	End plates allow the blade to hold material in to drag from one spot to another.
<b>Cylinder cushion valve (optional)</b>	Cylinder cushion valve protects the cylinders and blade from sudden impacts by allowing hydraulic fluid to escape vs. blowing seals.
<b>Single or dual gauge wheels (optional)</b>	Gauge wheels position the height of the blade to aid in grading.