



RB16 & RB26 Series

Features	Benefits
Warranty	One year parts & labor. See warranty page for complete details.
RB16 working widths (60", 72", 84") RB26 working widths (72", 84", 96")	Choice of three sizes per Series to pick from.
RB16 Series: 20-40 hp (15-30 kW) RB26 Series: 25-60 hp (19-37 kW)	RB16 Series fits a wide variety of small tractors between 20 & 40 hp. RB26 Series fits a wide variety of small tractors between 25 & 60 hp.
Quick Hitch	Fits Land Pride Quick Hitch.
Blade angles left and right up to 45° in forward position and 30° in reverse position	(7 Forward positions in 15° increments and 3 reverse positions in 30° increments) Many angles for diverse jobs and results.
Blade offsets left or right 12" (30 cm)	Manually move moldboard to cover either tractor tire.
Blade tilts up or down up to 15°	(5 positions: Center, 2 clockwise, and 2 counterclockwise) Allows operator to do simple tasks such as putting a crown in the middle of a road to making V-type ditches.
Formed rolled moldboard RB16 Series: 14" (36.6 cm) high RB26 Series: 17 1/2" (44.5 cm) high	Rolled moldboard allows material to flow easily, which means less drag, less hp. 14" (36.6 cm) High moldboard for good capacity. 17 1/2" (44.5 cm) High moldboard for excellent capacity.
Reversible cutting edge	For twice the life.
Park stand	Store unit with front of hitch off the ground, allows for easier hook-up.
End plates (Accessory)	End plates hold material in to be moved.
Skid shoes (Accessory)	Help protect from hitting low obstructions by keeping the cutting edge off the ground. Set skid shoes to clear obstructions like manhole covers and street cracks.
Rake assembly (Accessory)	The blade assembly can be removed from the main frame and a rake assembly attached to give the Land Pride Rear Blade versatility.
Hydraulic angling (Accessory)	Makes rotating blade angle horizontally easy with infinite number of angles available between 0° and 45° clockwise and counterclockwise.