

**STB15 Series**

Features	Benefits
<b>Reinforced 10 gauge moldboard design</b>	Provides added strength and durability.
<b>Choice of 60", 72", 84" or 96" working widths</b>	Allows customers to choose the blade that meets their operational needs.
<b>Double-acting angling cylinders (dual)</b>	Easily enables up to 30 degrees of angling to left or right distributing the load where you want it to go.
<b>Trip design with springs</b>	Protects the structural integrity of the blade while still maintaining load control no matter what the bottom edge encounters.
<b>Easy-attaching mounting system</b>	Adapted for tractor loaders with quick-attach front mounting plates.
<b>Replaceable bottom wear edge</b>	Offered in steel or heavy-duty poly construction to match ground & surface operating conditions.
<b>Skid shoes</b>	Offered as standard equipment. Establish lower limits of blade operation to prevent surface gouging or cutting too deep. Also provides protection to the moldboard as cutting edge wears.
<b>Blade marker</b>	Provides operator with improved awareness and visibility of outermost edges of the blade bottom to prevent unwanted contact with ground obstacles.
<b>Optional top mounted rubber deflector</b>	Helps prevent snow from over-topping the moldboard in deeper snow conditions.
<b>Side float</b>	Allows the blade to follow the ground contour.
<b>Locking system</b>	Allows for light blading.
<b>Cushion valve</b>	Helps protect the moldboard and cylinders in the event an obstruction is hit, by allowing hydraulic fluid to bypass the cushion valve and flow back to the tractor.