

STB1060 & STB1072 Models

Features	Benefits
Reinforced 12 gauge moldboard design	Provides added strength and durability.
Choice of 60" or 72" working widths	Allows customers to choose the blade that meets their operational needs.
Double-acting angling cylinder (single & dual)	Easily enables up to 30 degrees of angling to left or right distributing the load where you want it to go.
Trip design with springs	Protects the structural integrity of the blade while still maintaining load control no matter what the bottom edge encounters.
Easy-attaching mounting system	Adapted for tractor loaders with quick-attach front mounting plates.
Replaceable bottom wear edge	Offered in steel or heavy-duty poly construction to match ground & surface operating conditions.
Skid shoes	Offered as standard equipment. Establish lower limits of blade operation to prevent surface gouging or cutting too deep. Also provides protection to the moldboard as cutting edge wears.
Blade marker	Provides operator with improved awareness and visibility of outermost edges of the blade to prevent unwanted contact with ground obstacles.
Locking system	Allows for light blading.
Optional top-mounted rubber deflector	Helps prevent snow from over-topping the moldboard in deeper snow conditions.
Cushion valve	Helps protect the moldboard and cylinders in the event an obstruction is hit, by allowing hydraulic fluid to bypass the cushion valve and flow back to the tractor.