

**LR16 & LR26 Series Landscape Rakes**

Features	Benefits
<b>60", 72", 84", 96" Working Widths</b>	Meets a wide range of customer needs.
<b>LR16 Series: 20-40 Tractor HP Range LR26 Series: 25-60 Tractor HP Range</b>	Fits many tractors with a Cat. I 3-Point hitch.
<b>Quick Hitch Adaptable</b>	Fits Land Pride Quick Hitch for a quick and easy one person hook-up.
<b>Retractable Park Stand</b>	Keeps frame off the ground and makes hook-up easier.
<b>3 1/2" Pivot Tube</b>	Heavy frame tube. Heaviest in its class.
<b>16 1/2" Rake Height</b>	Can move a great deal of material.
<b>Rake Teeth Support Channel</b>	Design with channel support. This design supports the rake teeth better than competitor models. Prevents teeth entanglement and keeps attachment hardware from working loose.
<b>5/16' x 1" High Carbon Spring Steel Teeth</b>	Sized to eliminate premature bending and tooth breakage. Constructed of materials that have "memory" to spring back to shape.
<b>Individual Replaceable Teeth</b>	Makes replacing a damaged tooth quick and easy without removing all of the teeth.
<b>Angle 7 Positions</b>	Versatility in operation. Vary how much material to move.
<b>Hydraulic Angle Kit (Accessory)</b>	Allows the operator to change rake angle from the tractor seat.
<b>Dual Gauge Wheels (Accessory)</b>	Gives operator better depth control. Wide & narrow wheels available.
<b>Flip-Down Grader Blade with End Plates (Accessory)</b>	Enables the rake to perform light blading duties for moving and leveling dirt as well as other materials. Grader blade can be flipped up when not in use.
<b>Rear Blade Attachment (Accessory)</b>	The rake assembly can be removed from the main frame and a Rear Blade attached to give the Land Pride Rake versatility.