

**PTS500 & PTS700 Broadcast Spreaders**

Features	Benefits
<b>Large hopper capacity</b>	To meet specific customer needs.
<b>Spin-type broadcast</b>	For even spreading and productive coverage up to 40 ft.
<b>One piece molded polyethylene hopper</b>	Plastic construction to eliminate corrosion. Seamless for accurate and consistent emptying.
<b>Heavy-duty tubular frame</b>	Supports the weight when full.
<b>Pull type hitch</b>	For attachment to a wide range of tractors and vehicles.
<b>Adjustable tongue</b>	Keeps hopper level at varying hitch heights.
<b>Tow hitch</b>	Handles up to 800 pounds towing capacity. (50 pounds maximum tongue weight.)
<b>Greasable Axle</b>	Helps with longevity of axle.
<b>Shielded Front</b>	Prevents spreading of material in front of spreader.
<b>Stainless steel distributor vanes</b>	Protects from corrosive material to enhance longevity.
<b>Adjustable distributor vanes</b>	Four adjustable positions to obtain maximum spreading precision and uniformity.
<b>Stainless steel orifice doors</b>	Protects from corrosive material enabling doors to operate smoothly.
<b>Plated adjustment levers</b>	Protects from corrosive material to enhance longevity.