

RTR05 Series

Features	Benefits
American made	Many tillers are imported. American made means better parts availability.
Reverse tilling action	Reverse action 'sucks' tiller into ground, does not walk on top of hard ground like forward rotation tillers can.
Tractor horsepower range	17-26 hp
Gearbox warranty	2 Years on housing, seals, & bearings. (Shows our confidence in the product.)
Working widths	42" and 50" to meet specific customer needs.
5" Digging depth	For deep soil penetration.
Clevis lower hitch	Provides additional strength and easy one person hook-up.
Fits Land Pride Quick Hitch	Allows for quick and easy one person hook-up. An additional driveline may be required.
Adjustable park stand	Allows for easy hook-up and storage.
Adjustable skid shoes	Control depth with seven adjustments.
Formed rear deflector	Keeps dirt in and leaves a level finish. Forming gives deflector additional strength. Adjustable deflector allows for various finish results.
Front deflector	Front deflector is flexible to take the beating from rocks or debris.
4 "C" shaped heat-treated tines per flange	'C' Shaped tines require less horsepower to move through the ground.
Solid rotor shaft	1 3/4" Solid steel rotor shaft for strength.
13" Rotor swing diameter	For deep tilling and turning the soil over faster.
Double lip seal on rotor bearing	Double lip seal helps keep the dirt out and the grease in.
Fully shielded shear pin or slip-clutch driveline	Protects the gearbox and rotor shaft upon hitting obstructions. Slip-clutch saves having to replace shear-pins.
#80 Drive chain enclosed in oil bath	Heavy drive chain stretches less, and oil bath keeps wear to a minimum.
Stamped chain cover	Stamped forming gives the chain cover strength.