

RCP(M)26 & RCP(M)30 Series (Parallel Arm)

Features	Benefits
Tractor hp Range RCP(M)2660 RCP(M)3060	Designed for 75 minimum hp tractor with minimum weight of 8,000 lbs. Designed for 95 minimum hp tractor with minimum weight of 12,000 lbs.
Gearbox hp Rating	150 hp
3 Point Design	Does not tie up a tractor. Three point hook up is easy to hook up and remove from tractor.
Cutter Deck Visibility	Visibility of the cutter deck is captured from the operator's seat. Easy to see operation. Operator does not have to look behind.
Factory Assembled	Arrives ready for the customer, saves time and money. (Excluding fluids and hydraulic valve)
Grease Ports	All grease ports are easily accessible for servicing.
10' Transport Width	Folds up close to the tractor. No weight brackets or decks hanging away from the tractor. Typically, not much wider than the tractor, which means safer transporting.
Parallel Arm Design	Three cylinders used in a parallel arm design allows any cylinder to be adjusted without changing the position of the others. Means less positioning.
Long Horizontal Reach RCP(M)2660 = 15'-6" (186") RCP(M)3060 = 18'-10" (226")	Good access for reaching vegetation far away from the tractor. Better access for reaching vegetation far away from the tractor.
Above Grade Vertical Reach RCP(M)2660 = 11'-5" (137") RCP(M)3060 = 13'-5" (161")	Good access for reaching up embankments and cutting low over hanging limbs. Better access for reaching up embankments and cutting low over hanging limbs.
Below Grade Reach RCP(M)2660 = 9'-1" (109") RCP(M)3060 = 11'-0" (132")	Good access for reaching down embankments. Better access for reaching down embankments.
180 Degree Operating Tilt Arc	Cutter head can be positioned to reach different angles.
Cat. 2 & 3; 540 or 1000 rpm	Fits a wide variety of tractors.
35 Gallon Oil Reservoir	Large reservoir maintains optimum fluid temperatures and also serves as counterweight.
2" Cutting Capacity	Ideal for trimming brush.
High Blade Tip Speed	15,000 fm tip speed means cleaner cutting.
Two Parking Stands	Easy and level storage, makes it easy for hooking to tractor.
In-line Filter	Cleans hydraulic fluid before it re-enters the reservoir.
Shut-off Valve	Permits maintenance with minimum oil loss.
Built-in Auxiliary Weight Rack on Left Side	Suitcase weights can be added to left side for balance. Able to choose the weight bracket to match various types of suitcase weights.
Oil Pressure Gauge	Easily monitor oil pressure for optimum performance of unit.
Hydraulic Breakaway	Allows the parallel arms to pivot backwards to avoid obstacles and to protect cutter deck and parallel arms. Parallel arms are pivoted back to normal operating position with the hydraulic breakaway cylinder.
Flow Control Valve	Compensates for various tractor hydraulic systems so proper hydraulic fluid pressure can be maintained. (Used only with solenoid control Option.)
Solenoid Controlled Cylinders	Allows cutter to be used on tractors with only two hydraulic duplex outlets. Response time is faster than tractor controls making it an excellent choice when frequent changes to deck position. (Used only on Solenoid Control and Independent Control Options)
Gauge Wheels Option	Deck floats on gauge wheels eliminating frequent deck positioning and vigilant watch for changes in ground contour under the tractor and deck.
Independent Control Option (Self-Contained Hydraulics)	Self contained hydraulic system eliminates the tractor/RCP hydraulic incompatibility. This option uses the RCP hydraulic system to operate the cutter. Tractor needs one set of hydraulics to operate the breakaway cylinder.
Kubota 3-Point Stabilizer Kit	Makes the RCP2660 Parallel Arm Rotary Cutter a match fit for Kubota tractor model numbers M126GX, M135GX, M6-141, and M6-141.
Slow Moving Vehicle Mounting Socket (Standard) Slow Moving Vehicle Sign (Accessory)	Mounting socket receives most slow moving vehicle signs equipped with a mounting blade for ease of attachment and removal when transporting on a truck or trailer. Slow moving vehicle sign is offered as an accessory when the tractor's slow moving vehicle sign and mounting blade does not fit the cutter's standard mounting socket.