

HRS3025

Features	Benefits
540 rpm Cat I & II three-point mounting	Adapted for service on a wide range of tractors.
Low horsepower requirements	52 Horsepower requirement for approximately 25 gpm @ 3000 PSI and 540 rpm
35 Gallon self contained reservoir with 10 micron filter	Provides more than ample amounts of clean and cool hydraulic fluid for even the most demanding applications.
Steel construction on Hydraulic Tank	Provides for long service life in harsh environments.
Standard reversing solenoid	Allows powered implements, motors, and cylinders to be reversed for expanded range of performance capabilities.
Standard pressure relief valve	Protects hydraulic system from overloads or unanticipated stalls.
Standard case drain port	Enables attachment and usage with implements equipped with and requiring case drain return lines.
Standard compliment of hydraulic fittings & two 23'-9" of hydraulic hoses supplied	Enables ready attachment and adaptation to a wide range of tractors and applications.
Multi-functional electronic remote tether control	Enables forward and reverse continuous flow or intermittent forward or reverse flow from the tractor seat or on the ground.
Driveline connected	Easy hook-up to rear PTO tractor shaft.
Oil cooler	For oil cooling when necessary. Included with hand valve & solenoid valve options. Optional with no valve option.
Integral storage stands	Provides for easy installation and removal from the tractor and clean and convenient long term storage.