



**RCF3672 Model**

Features	Benefits
<b>Surpassed rugged industry standards</b>	All Land Pride Cutters have been designed and tested and meet rigorous voluntary testing procedures specified by ANSI.
<b>5 Year gearbox warranty</b>	A rugged heavy built gearbox capable of handling heavy cutting applications. Shows our confidence in the gearbox integrity.
<b>190 Horsepower gearbox</b>	A rugged heavy built gearbox capable of handling heavy cutting applications.
<b>Cat. 5 driveline with 4-plate slip-clutch</b>	Slip-clutch driveline offers convenience for continual work.
<b>Dual position clevis type 3-Point floating top link</b>	Permits deck to follow the terrain for an even cut. Additional set of holes for tractors with shorter top links.
<b>Lower clevis type 3-Point hitch</b>	Allows for ease of hook-up to tractor. Also adds additional strength allowing for an even pull from the tractor's lower arms, vs. pulling on a single pin design.
<b>Heavy deck construction with 3/16" deck top &amp; 1/4" side skirts</b>	Strong heavy deck material for rugged use.
<b>Box tubing deck supports</b>	Makes for a stronger rigid deck.
<b>Fully welded deck</b>	Adds additional strength.
<b>Round back design</b>	Helps discharge grass better than enclosed or partially enclosed cutters.
<b>13 3/8" Deck height</b>	Allows cutter to handle heavy cutting conditions.
<b>2" to 12" Cutting height</b>	Provides for a wide range of cutting conditions.
<b>High cutting capacity</b>	Can cut brushy areas with saplings up to 4".
<b>Skid shoes</b>	Provides sidewall reinforcement and protection to bottom of sidewall.
<b>1/2" x 4" Heat-treated free swinging blades</b>	Free swinging protects from obstructions. Heat-treated offers longer life.
<b>Splined blade bar hub</b>	Allows for tight positive fit of stump jumper and blade bar to gearbox output shaft.
<b>3/16" Plate stump jumper</b>	Standard round stump jumper slides over stumps, rocks, and debris.
<b>High blade tip speed, 14,861 fpm</b>	Ensures clean cut.
<b>15" Laminated tailwheel</b>	Laminated material is long lasting in rough conditions and can't go flat.
<b>1 1/2" Heavy-duty spindle on tailwheel</b>	Tailwheels take a beating, spindle gives the strength to protect tailwheel assembly.
<b>Optional guarding</b>	Protect against flying debris. Customer can choose to include single chain, double chain or rubber guarding on the front and single chain or double chain guarding on the back.