



RC(M)3715 & RCG(M)3715 Models

| Features | Benefits |
|--|--|
| Surpassed rugged industry standards | All Land Pride Rotary Cutters have been designed and tested and meet rigorous voluntary testing procedures according to ISO 4254-13. |
| Factory assembled | Arrives for quick and easy set-up. Minimal time wasted setting or prepping the unit. |
| 5 Year gearbox warranty | Shows confidence in gearbox integrity. |
| Rugged heavy built gearboxes | Capable of handling heavy cutting applications. |
| Gearbox seal protection | Gearbox bottom seal protection for longer bearing life. |
| 2 Piece driveline shields | Driveline grease zerks are easier to access. |
| Low hitch weight on tractor tongue | Ideal for smaller hp tractors by reducing the amount of weight on the drawbar. |
| Narrow A-frame hitch | Allows for a tighter turning radius. |
| Adjustable park jack angle | Park jack can be adjusted to be perpendicular to the ground. |
| Adjustable driveline hanger | Serves as support rest for the driveline when the cutter is unhooked from the tractor. Assist operator when attaching driveline to tractor power take-off shaft. |
| Input driveline: Cat. 6 CV | Driveline is matched just right for capacity of tractor. Constant velocity (CV) U-joint allows for 80 degree turns without doing damage to the driveline. |
| Drivelines with slip-clutches: Cat. 4 intermediate Cat. 4 or Cat. 5 wings | Driveline is sized right for the intended cutting capacity. Slip-clutches will slip under load to minimize twist damage to driveline profiles. |
| Grease zerks on end caps of driveline | Intermediate and wing driveline cross journals are easier to grease. |
| High blade tip speed | Allows clean cutting of material. |
| 6" Blade overlap | Eliminates skipping during turns. |
| 3/16" Round stump jumper | Standard thick stump jumper material keeps damage to a minimum. |
| Smooth top design | Reduces accumulation of debris and is easier and faster to clean. |
| Tops of decks are 100% welded | Makes center decks and wing decks stronger. |
| 1/4" Sidewall thickness | Increased thickness reduces damage from objects being thrown into deck sidewalls. |
| Beveled skid shoes on wings | Reduces gouging the ground when turning. |
| LED signal lights | LED lights are bright, long lasting, and resist vibration, unlike incandescent lights. |
| Hinged wing sections | Allows cutter to follow terrain. Ideal for rough ground where hillsides, ditches, and hollows can cause uneven cutting. |
| 1" Solid hinge rods | Larger diameter hinge rod provides greater strength in the hinge area. |
| Wing transport lock pins | Transport lock pins will hold wings in folded position in the event of hydraulic loss. |
| Enclosed dual 1" leveling rods | Cutter pulls equally on the rear axle while traveling over rough terrain. |
| 5-Bolt hubs | 5-Bolt hubs makes the wheel assembly more durable and longer lasting. |
| Drain holes in wheel rims | Allows water to drain from wheels mounted on folded-up wings. Helps prevent paint deterioration and rusting to the wheel rims. |
| Spring cushioned center-axle | Protects unit from bumps and ground shock. |
| Replaceable individual wheel spindles | Spindles can be replaced when damaged without replacing entire axle assembly. |
| Wheel options | Laminated tires: Eliminates flats. Air-filled tires: Give better cushion while transporting. Foam-filled tires: Give better cushion while transporting and can't go flat. |
| LP Performance hitch option | Great for uneven terrain, reduces drawbar wear. Hitch pivots freely up and down and pivots about the tractor drawbar. |
| Bar-tite hitch option | Ideal for extreme conditions. Clamps tight to drawbar eliminating drawbar wear. |
| Maintenance free tongue & axle pivots | Self lubricating journal bearings make for less maintenance. |
| Color coded hydraulic hose handles | Easy hose identification & sturdy handle to easily connect & disconnect from tractor. |
| 4 lip purgeable metal backed wheel hub seal | Seals make it harder for water & debris to enter the hub and grease to leave the hub. Metal backing prevents sticks and twine from destroying the seal lips. |
| Greaseable cast steel continuous hinge | Cast steel hinges make a strong connection & are easy to lubricate. |
| Galvanized decks on RCG models | Durable rust protection for harsh conditions. |