

GB25 & GBE25 Series

Bucket	
Features	Benefits
Grade 50 high strength steel shell 3/16" (5 mm) thick	Improved strength & wear versus mild steel
Five 1/2" x 5" (13 mm x 127 mm) bottom wear plates	Extends bucket life
Reinforced bucket corners & side edges	Adds strength & extends bucket life
Drilled cutting edge 5/8" x 6" (16 mm x 152 mm)	Accepts optional bolt on cutting edge
Optional bolt on cutting edge 5/8" x 6" (16 mm x 152 mm)	Reversible and replaceable; extends life of cutting edge
Upper torque tube/lower torque channel	Prevents twisting
Three widths available	Fits wide range of tractors: 90" (2.29 m), 96" 2.44 m), & 108" (2.74 m)
Struck capacity 1.0-1.2 Cu. Yd. (0.76m³-0.92m³)	Allows high volume material handling
Universal Quick-Attach mount	Allows grapple to be installed/removed quickly
Grapple	
Features	Benefits
High strength cast grapple tines	Stronger and better looking than welded tines
Tubular steel construction	Resists twisting
Parking stands	Allows grapple to be stored upright when not in use
Spill guard	Helps contain loose material
Dual cylinders 3" @ 3500psi (7.6 cm @ 24132 kPa)	Large cylinders handle high pressure & loads
Hose kit included	Hoses provided to center tees or valve
Optional lock valve	Prevents hydraulic bleed-off / improves cylinder control
Quick release grapple	Four pin mount system
Large 84" (2.13 m) opening	Handles large bales and high volumes of material
Greasable pivot points	Extends grapple life