

DB2660 DITCH BANK ROTARY CUTTER

HP REQUIRED
75 HP Min.

CUTTING CAPACITY
2"

HITCH
Cat. 2 & 3

CUTTERS



	DB(M)2660
Horsepower	75 HP; Min. Tractor Weight 7,000 lbs.
Hitch	Cat. 2 Std., Cat. 2 & 3 QH Clevis Type Lower Hitch
Working Width (cm)	58" (147)
Min. Transport Width	10'1"
Min. Tractor Weight - lb	7,000
Weight - lb (kg)	1,788 (811)
Tractor Hydraulics Req'd	See Specific Model
Hydraulic Pump Input	540 RPM or 1000 RPM
Hydraulic Oil Capacity	35 Gallons
Hydraulic Oil Flow	15 GPM
Hydraulic System	2 Duplex Required
Overload Protection	Relief Valve
Oil Cleansing	Return Line Filter, Replaceable
Oil Check	Dipstick
Min. Cutting Height	Depends on 3-Pt Height
Cutting Capacity	2" Diameter
Horizontal Extension	32" Maximum
Max. Horizontal Reach from Tractor Center	13'2"
Operating Tilt Arc	175 Degrees
Deck Thickness	10 Gauge
Safety Guards	Rubber, Single or Double Chain
Blades	2 Each, 1/2" x 4"
Blade Bolt	Keyed with Hardened Flatwasher & Lock Nut
Blade Tip Speed	15,600 fpm
Blade Rotation	Clockwise
Dishpan	3/16" x 21" Round, Dish Shaped
Driveline	Cat. 4
Storage	Parking Stand
Options	Rear Tailwheel, Side Gauge Wheel
Transport Lights	Standard
Colors	

Quickly reach inclines.

Land Pride's DB2660 Ditch Bank Rotary Cutter enhances our growing line of Rotary Cutters. This new hydraulic-driven cutter boasts a number of features that will make mowing ditch banks, pond dams, or other hard to reach inclines fast, easy, and efficient.

Built for either 540 or 1000 RPM tractors, the DB2660 features a 58" cutting width, 2" cutting diameter, and 32" cutting reach. The 1/2" by 4" blades rotate clockwise at 15,000 fpm, directing debris away from the tractor. Minimum cutting height is dictated by the tractor's 3-pt height.



Large 35 gallon oil reservoir maintains optimum fluid temperatures and also serves as a counterweight.



Built-in auxiliary weight rack is located on the left side close to the machine for ballast.



Optional side gauge wheels allow deck to float, eliminating frequent deck positioning.