

GS05/15/25 SERIES GRADING SCRAPERS

HP REQUIRED
17-90 HP

HITCH
Cat. 1 & 2



DIRTWORKING

A low cost alternative for road grading applications.

Land Pride Grading Scrapers simply and quickly move dirt or aggregate from high spots to low spots making them extra user-friendly and a low cost alternative for road grading applications. Simply setting a properly adjusted Grading Scraper on the ground and driving forward enables the operator to grade off high spots and fill in ruts at low spots on unimproved roads and lanes with little or no manipulation of the tractor's 3-Point hitch controls. Unlike a rear blade, they require no adjustment of blade angling or offset positions.



3-Position scarifier shanks allow the scraper to be adjusted to desired amount of calibration and guarding action. Hardened tips assure long service life.



Replaceable and reversible full length skid shoes make for easier operation and long unit life.



Reversible, heat-treated, high-carbon steel grading blades offer excellent wear resistance and long service life.

	GS0548	GS0560	GS1548	GS1560	GS1572	GS2572	GS2584	GS2596
Horsepower	17-33 HP		20-50 HP		25-50 HP		40-90 HP	
Hitch	Cat. 1		Cat. 1			Cat. 1 & 2		
Working Width (cm)	48" (122)	60" (152)	48" (122)	60" (152)	72" (184)	72" (183)	84" (213)	96" (244)
Side Panel Thickness	3/16" Thick with 1-1/2" Formed Edges		3/16" Thick with 2-3/4" Formed Edges			1/4" Thick with 2-3/4" Formed Edges		
Front Main Beam & Scarifier Support	4" x 3" x 1/4" Reinforced Heavy Wall Tubing; 3" x 2" x 3/16" Heavy Wall Tubing		4" x 4" x 5/16" Reinforced Heavy Wall Tubing; 2" x 2" x 3/16" Heavy Wall Tubing			4" x 4" x 5/16" Reinforced Heavy Wall Tubing; 3" x 3" x 3/16" Heavy Wall Tubing		
Skid Shoe Dimensions	1/4" Thick x 1-1/2" Wide x 40" Long		3/8" Thick x 2-3/4" Wide x 44" Long			3/8" Thick x 2-3/4" Wide x 50-1/4" Long		
Scarifier Shank Construction	3 Position		Heat Treated 4-Position Shank with Dimpled-on Hardened Tips					
Cutting Edges	3/8" x 6'		Two 1/2" x 6" High Carbon Heat Treated Blades; Reversible & Replaceable					
Cutting Edge Adjustment	Fixed		Infinite Vertical Adjustment from Level Grade to 1-1/2" Below Grade					
Weight - lb (kg)	310 (141)	350 (159)	437 (198)	511 (232)	594 (269)	728 (330)	796 (361)	864 (392)
Colors								

Rear cutting blades available as an accessory.



*See dealer for complete warranty information.