

RC36 SERIES OFFSET/FOLDING ROTARY CUTTERS

HP REQUIRED
70-160 HP

CUTTING CAPACITY
2"

HITCH
Pull-Type

CUTTERS



| | RC3614 | RC3620 |
|--|---|---|
| Horsepower | 70-160 HP | |
| Hitch | Pull-Type; Standard Clevis, LP Performance Self-Leveling, Pintle, Ball, Bar-Tite | |
| Working Width (cm) | 14' (426) | 20' (607) |
| Overall Width | 15' | 20' 10" |
| Min. Transport Width | 8' 9" | 9' 11" |
| Overall Length | 17' 6" with Laminated Tires | |
| Machine Weight - lb (kg) | 5,990 (2717) | 6,680 (3,030) |
| Cutting Height | 2" - 12" | |
| Cutting Capacity | 2" Diameter | |
| Tongue Weight - lb | 2,220 | 1,750 |
| Max. Turning Angle | 80° with CV | |
| Deck Height | 13" | |
| Deck Thickness | 10 Gauge | |
| Deck Shock Protection | Spring Cushioned | |
| Deck Rings | Optional | |
| Side Thickness | 1/4" | |
| Chain Guards Front & Rear | Double Optional | |
| Skid Shoes | Wings & Center, Replaceable | |
| Blades | 1/2" x 4" High Lift | |
| Blade Bolt | Keyed with Hardened Flatwasher & Lock Nut | |
| Blade Tip Speed (Feet per minute) | 540 Center | 16,000 fpm |
| | Wings | 16,000 fpm |
| 1000 Center | Wings | 16,500 fpm |
| | Wings | 16,500 fpm |
| Blade Overlap | 6" | |
| Dishpan | 10 Gauge Round, Dish Shaped w/ 1" x 4-1/2" Blade Bar | |
| Hydraulics | Wings | 3" x 12" Cylinder |
| | Center | 2-3/4" x 8" RH Wing-3" x 8", LH Wing-3-1/4" x 8" |
| Gearbox Rating[^] | 540 RPM or 1000 RPM: 250 HP Divider, 150 HP Ctr & Wings | |
| Gearbox Output Shaft | 2" | |
| Gearbox Input Shaft | 1-3/4" 20 Spline | |
| Input Driveline | Cat. 6 CV | |
| Connecting Drivelines | Cat. 4 Slip Clutch | |
| Tires | 21" Laminated RC3614: 5 or 6 RC3620: 6 or 8 29" Used Aircraft 27" Foam-Filled | |
| Transport Lights | Standard | |
| Colors | | |

Holds up to Tough Conditions.

Land Pride's RC3620 is the ideal Rotary Cutter for grassy fields, pastures, waterways, buffer strips, and set-aside acres and handles saplings up to 2" in diameter. With tip speeds of 16,000 to 16,500, gearboxes rated at 250 HP and 150 HP, 1-3/4" input shafts, 2" output shafts, and optional CV drivelines, this unit will make quick and efficient work of the largest jobs.

Also available as a 14' offset model: RC3614.



10 Gauge stump jumper is backed with a 1" x 4-1/2" thick blade mounting bar to protect the gearbox seal and output shaft.

7 YEAR
LIMITED GEARBOX
WARRANTY*



Rephasing lift cylinders allow cutter to be leveled using hydraulic cylinders versus mechanical turnbuckles.