

# RC5014 14' FOLDING ROTARY CUTTERS

HP REQUIRED  
90-250 HP

CUTTING CAPACITY  
3"

HITCH  
Pull-Type

CUTTERS



		RC5014
<b>Horsepower</b>		90-250 HP
<b>Hitch</b>		Pull-Type; Standard Clevis, LP Performance Self-Leveling, Pintle, Ball, Bar-Tite
<b>Working Width (cm)</b>		13' 6"
<b>Overall Width</b>		14' 7"
<b>Min. Transport Width</b>		8' 9"
<b>Overall Length</b>		19' 3"
<b>Machine Weight - lb (kg)</b>		7,282 (3,303)
<b>Cutting Height *</b>		2" - 14"
<b>Cutting Capacity</b>		3" Diameter
<b>Tongue Weight - lb</b>		2,300
<b>Max. Turning Angle</b>		80° with CV
<b>Deck Thickness</b>		10 Gauge Top & Bottom
<b>Deck Height</b>		10-1/2"
<b>Deck Shock Protection</b>		Spring Cushioned Axle
<b>Deck Rings</b>		Optional
<b>Side Thickness</b>		1/4"
<b>Safety Guards (must choose)</b>		Single or Double Chain
<b>Skid Shoes</b>		1 on Wing and Weight Box, 2 on Center Section, Replaceable
<b>Blades</b>		1/2" x 4" High Lift
<b>Blade Bolt</b>		Keyed with Hardened Flatwasher & Lock Nut
<b>Blade Tip Speed (Feet per minute)</b>	<b>540 Center</b>	17,377 fpm
	<b>Wings</b>	17,329 fpm
	<b>1000 Center</b>	18,165 fpm
	<b>Wings</b>	18,317 fpm
<b>Blade Overlap</b>		6"
<b>Dishpan</b>		1" Plate Diamond Blade Bar; Optional 3/16" Round Dishpan
<b>Hydraulics</b>	<b>Wings</b>	3-1/2" x 12"
	<b>Center</b>	4" x 8"
<b>Gearbox Rating<sup>A</sup></b>		540 RPM or 1000 RPM: 250 HP Divider, 225 HP Center & Wing
<b>Gearbox Output Shaft</b>		2-3/8"
<b>Gearbox Input Shaft</b>		1-3/4" 20 Spline
<b>Input Driveline</b>		Cat. 6 CV
<b>Connecting Drivelines</b>		Cat. 5 Slip Clutch
<b>Tires - 5 or 6</b>		21" Laminated, 29" Used Aircraft, 27" Foam-Filled
<b>Transport Lights</b>		Standard
<b>Colors</b>		

## Our largest offset cutter.

The RC5014 – Land Pride’s largest offset folding rotary cutter – makes quick work of roadsides 14-feet at a time. The offset allows the operator to travel next to the roadway in the same direction of travel as the traffic, increasing safety for the operator. The cutter features a heavy-duty Cat 6 driveline, heavy-duty gearboxes, and a high blade tip speed for a clean, uniform cut in most highway mowing operations.



**7 YEAR**  
LIMITED GEARBOX  
WARRANTY\*

10-1/2" Deck height handles heavy cutting, which reduces balling-up of cut material under the deck.



Skid shoes are reversible and replaceable - each side of the center section, the wing, and the weight box.



1" Solid hinge rods and greasable cast wing hinges provide years of dependable service.



Choice of used aircraft tires, with or without foam, or laminated tires.

\*Maximum cut height is dependent on tire options selected.