

RCD18 SERIES OFFSET ROTARY CUTTERS

HP REQUIRED
35-60 HP

CUTTING CAPACITY
1-1/2"

HITCH
Cat. 1



CUTTERS

Right for the Job.

The RCD1884 is a smooth-top, offset cutter that performs best in grass-only applications. Being dual spindle, the cutter is shorter in length than single spindle 84" cutters; the reduced length allows for better maneuverability in tight spaces. The 10" offset makes the RCD1884 a good solution for applications that require cutting close to buildings, fences, or other obstacles that might be found in orchards, parks, or rights-of-way.

- Deep-deck design
- All-welded deck
- Short coupled for tight spaces
- Clevis-style hitches for easy hook-up

5 YEAR
LIMITED GEARBOX
WARRANTY



Hitch offsets 10" to the right to cover your tractor tire and get closer to obstructions.



Dual gearboxes allow lower horsepower tractors to cut 84" swaths.



Intermediate driveline transfers loads from center box to wing box to ensure proper cut quality.

| | RCD1884 |
|-----------------------------|--|
| Horsepower | 35-60 HP |
| Hitch | Cat. 1 QH |
| Working Width (cm) | 84" (213) |
| Overall Width | 86.5" |
| Overall Length | 80.5" |
| Weight - lb (kg) | 900 (408) |
| Cutting Height | 2"-12" |
| Cutting Capacity | 1-1/2" Diameter |
| Offset | 10" |
| Deck | All Welded |
| Deck Thickness | 10 Gauge |
| Deck Height | 11-5/8" |
| Safety Guards | Front: Rubber or Chain Rear: Metal Band |
| Skids | Weld-on |
| Additional Skids | Bolt-on |
| Blades | 2 Each, 1/2" x 4" x 16" Heat Treated Free Swinging Alloy Steel Suction Blades |
| Blade Bolt | Keyed with Hardened Flat Washer & Lock Nut |
| Blade Tip Speed | 11,693 fpm |
| Dishpan | 10 Ga. x 24", Round, Dish Shaped |
| Gearbox Rating ^A | 90 HP Main; 45 HP Side |
| Gearbox | 540 RPM, Beveled Gears, Cast Iron Housing |
| Driveline | Cat. 3 with 2-Plate Slip-Clutch |
| Tailwheels | 15" Laminated Tire or 4" x 16" Molded Rubber |
| Colors | |

QUICK HITCH
SYSTEM

^{*}See dealer for complete warranty information. [^]Based on field performance.