

# RCR25 SERIES DUAL SPINDLE ROTARY CUTTERS

HP REQUIRED  
40-110 HP

CUTTING CAPACITY  
1-1/2"

HITCH  
Cat. 1, 2 & 3

CUTTERS



## A perfect fit for any size farm.

The RCR25 Series is well-suited for medium sized chores and is designed for performance in pastures, set aside acres, roadsides, and routine farm maintenance.

**Pull-Type:** The Pull-Type model features two leveling rods that connect the rear axle to the front tongue. This enables the deck to stay level over uneven ground conditions. The height controlling axle cylinder is attached to two deck springs that help cushion the cutter in rough terrain. A narrow tongue on Pull-Type allows for tight turns.

**3-Point:** The 3-Point unit utilizes two casting laminated tailwheels for smooth, trouble-free performance. The easy to attach clevis hitch is designed to fit Cat. 1 or 2 tractors on the 96" model, and Cat. 2 or 3 tractors on the 10' model.

- Slip-clutch and impact absorbing cross shafts to outer gearboxes
- Constant Velocity U-Joint option on 10' Pull-Type
- Slip-clutch protection on main driveline
- Fully welded 10 Gauge deck
- Round back design
- Chain or rubber shield option
- Replaceable skid shoes
- 1" x 4" Blade bar

**5 YEAR**  
LIMITED GEARBOX  
WARRANTY



Narrow tongue on Pull-Type allows for tight turns.

	RCR2596	RCR2510
<b>Horsepower</b>	Pull: 40-110 HP 3-Pt: 50-110 HP	Pull: 50-110 HP 3-Pt: 60-110 HP
<b>Hitch</b>	Cat. 1 & 2	Cat. 2 & 3
<b>Working Width (cm)</b>	7'10" (239)	9'10" (300)
<b>Overall Width</b>	8'3-3/4"	10'3-1/2"
<b>Overall Length</b>	Lift - 8'10", Pull - 11'8-3/4"	Lift - 9'4", Pull - 12'6"
<b>Weight - lb (kg)</b>	3-Pt: 1,380 (625) Pull: 1,665 (755)	3-Pt: 1,750 (793) Pull: 2,035 (923)
<b>Deck Thickness</b>	10 Gauge	
<b>Deck Height</b>	9-5/8"	
<b>*Safety Guards (choose)</b>	Front: Rubber or Chain Rear: Rubber or Chain	
<b>Skids</b>	Replaceable	
<b>Gearbox Rating<sup>^</sup></b>	210 HP Splitter 90 HP Outboard	
<b>Gearbox</b>	540 rpm, Cast Iron Housing, Beveled Gears	
<b>Cutting Height</b>	2" - 12"	2" - 10-1/2"
<b>Cutting Capacity</b>	1-1/2" Diameter	
<b>Blades</b>	1/2" x 4" Heat Treated, Free-Swinging Suction Blades	
<b>Blade Tip Speed</b>	14,592 fpm	17,749 fpm
<b>Dishpan</b>	3/16", Round, Dish Shaped	
<b>Driveline</b>	Plate Slip-Clutch	
<b>Tailwheel</b>	Lift-Type: 2 each, 4" x 8" x 15-1/4" Laminated Pull-Type: 2 each, 6" x 9" x 21" Laminated or 24" Aircraft Tires	
<b>Colors</b>		