

RS15/20 SERIES RIPPER SHANKS

HP REQUIRED
35-110 HP

HITCH
Cat. 1 & 2



DIRTWORKING

Fracture hardpan up to 27" deep.

Land Pride's heavy-duty 3-Point RS15 and RS20 Ripper Shanks are tillage tools perfect for fracturing compacted hardpan. The single-shank RS15 and dual-shank RS20 are capable of ripping the soil up to 27" deep. Both models feature high carbon 1.25" heat treated steel shank(s), heat-treated replaceable tips, shear pin protection, and a Cat 1 and 2 3-Point hitch. The RS20 also features adjustable row spacing to be just right for your application.



Multiple shank height mounting options helps large tractors go deep and smaller tractors get more transport clearance.



Shank tips feature 2" wide x 11-1/2" long ripper point with double chrome caps.

	RS15	RS20
Horsepower	35-80 HP	70-110 HP
Hitch	Cat. 1 & 2 3-Point (Quick Hitch Compatible)	
Width	40-5/8"	49"
Row Spacing	-	Up to 42"
Weight - lbs (kg)	210 (95)	332 (151)
Number of Shanks	1	2
Ripping Depth	24"-27"	
Park Stand	Standard	
Color		

QUICK HITCH
SYSTEM

*See dealer for complete warranty information.