

RTA25/35 SERIES ROTARY TILLERS

HP REQUIRED
25-95 HP

HITCH
Cat. 1 & 2

TILLERS



A contractor's dream.

Ideal for landscapers, gardeners, and contractors, the Land Pride RTA25 Series forward rotation Rotary Tillers prepare seedbeds for gardening or lawn planting. Rugged and dependable, the RTA25 features a heavy-duty driveline, a parking stand for easy hook-up, and optional down pressure springs apply pressure on the rear deflector, holding larger debris in the tines for better pulverization in tough leveling conditions.

With a 76" working width, and adjustable lower hitch clevises, taking out your tire track is usually achievable. This allows for less overlap needed, meaning less time in the tractor seat.



RTA35 SERIES: Ready to tackle the tough stuff.

The RTA35 Series is Land Pride's toughest tiller, built to withstand the rigors of commercial jobs. The 35 Series Tiller is designed to go all day, day after day, in the most demanding jobs. With a 19" rotor swing diameter, this tiller can turn over a lot of dirt without much getting in its way. The RTA35 is ideal for landscaping, nurseries, and commercial gardening applications.

	RTA2562	RTA2570	RTA3576
Horsepower	25-75 HP		35-95 HP
Hitch	Cat. 1		Cat. 1 & 2
Width-Endplate to Endplate (cm)	64" (162)	70" (178)	76" (193)
Overall Width	68"	76"	81-1/2"
Weight - lb (kg)	649 (294)	663 (301)	856 (388)
Number of Flanges	8	9	8
No. of Blades per Flange	6 C-Shape		6 C-Shape
Blade Spacing	7-7/8"		9"
Max. Tilling Depth	7"		7"
Skid Shoe Settings	6		6
Rotor Swing Diameter	17"		19"
Rotor Shaft Speed	220 rpm at 540 rpm PTO		204 rpm at 540 rpm PTO
PTO Driveline	Category 3 Heavy Duty Shear Bolt or Slip Clutch		Category 4 Slip Clutch
Gearbox	55 HP, 540 rpm, Cast Iron Housing, Drain Plug		75 HP 540 rpm, Cast Iron Housing, Drain Plug
Drive Chain	#100 High Tensile in Oil Bath		#100 High Tensile in Oil Bath
Sprockets	Hardened Teeth, Splined Center		Hardened Teeth, Splined Center
Colors			

See page 47 for reverse-till diagram.

QUICK HITCH SYSTEM

3 YEAR
LIMITED GEARBOX
WARRANTY