

# RTR05 SERIES ROTARY TILLERS

HP REQUIRED  
Up to 26 HP

TYPE OF HITCH  
Cat. 1



TILLERS

## Versatility to fit every need.

Our 05 Series Reverse Tine Rotary Tillers are perfect for popular subcompact tractors. If you are tilling your yard for reseeding or getting the garden ready for spring planting, turn your ground over efficiently with the best small tiller available!

- Cast iron bearing mounts
- Front rubber flap to keep material in
- Lower hitch clevises for easier hook up to tractor



The chain cover is stamped for strength. The formed rear deflector keeps material in and leaves a level finish and is adjustable allowing for various finish results.

**2 YEAR**  
LIMITED GEARBOX  
WARRANTY\*



Control depth with seven adjustments to the skid shoes.



Four "C" shaped heat-treated tines per flange require less horsepower to move through the ground.

**SOLID**  
ROTOR SHAFT  
**STEEL**

1-3/4" Solid steel rotor shaft provides strength.

	RTR0542	RTR0550
<b>Horsepower</b>	Up to 26 HP	
<b>Hitch</b>	Cat. 1	
<b>Width-endplate to endplate (cm)</b>	42" (107)	50" (127)
<b>Overall width</b>	46-1/2" (118)	54-1/2" (139)
<b>Weight - lb (kg)</b>	268 (122)	298 (135)
<b>Number of Flanges</b>	6	7
<b>No. of Blades per Flange</b>	4 C-Shape	
<b>Blade Spacing</b>	6-1/2"	6-3/4"
<b>Max. Tilling Depth ^</b>	6-1/2"	
<b>Skid Shoe Settings</b>	4	
<b>Rotor Swing Diameter</b>	13"	
<b>Rotor Shaft Speed</b>	230 rpm at 540 rpm PTO	
<b>PTO Driveline</b>	Category 2 Off-Center Shear Bolt or Slip Clutch	
<b>Gearbox</b>	26 HP, 540 rpm, Cast Iron Housing, Drain Plug	
<b>Drive Chain</b>	#80 High Tensile in Oil Bath	
<b>Sprockets</b>	Hardened Teeth, Splined Center	
<b>Colors</b>		

**QuickHitch**  
SYSTEM

\*See dealer for complete warranty information. ^ Tilling depth depends on conditions and fluffiness of tilled area.