

# RTA20/RTR20 SERIES ROTARY TILLERS

HP REQUIRED  
23-75 HP

HITCH  
Cat. 1



TILLERS

## We have traditional forward rotation...

Available in two popular widths, the Land Pride RTA20 Series Rotary Tiller effortlessly turns up hard-packed ground, leaving a perfect seedbed for gardens or grass. Suited for up to 50 HP tractors, this model fits a wide range of tractor owners, from landscapers or city and park maintenance operations to golf course superintendents.

## And the most popular reverse rotation...

The Land Pride RTR20 Series Rotary Tillers are just right for home gardening, landscape work, food plot maintenance, and light commercial use. Available in 64" and 72" widths, RTR20 Series Rotary Tillers feature a reverse tilling action for tough ground conditions. The reverse action of the rotor brings material up and over the top, burying heavier clods and small rocks, leaving the soil on top for a perfect seed bed.

Both models use standard Land Pride features like a strong stamped chain cover, adjustable rear deflector, heavy-duty driveline and parking stand – in the end the quality and dependability shine through.



	RTA2064	RTA2072	RTR2064	RTR2072
<b>Horsepower</b>	23-75 HP			
<b>Hitch</b>	Cat. 1			
<b>Width-Endplate to Endplate (cm)</b>	64" (162)	72" (183)	64" (162)	72" (183)
<b>Overall Width</b>	70-13/16"	77-7/8"	70-13/16"	77-7/8"
<b>Weight - lb (kg)</b>	689 (313)	734 (333)	748 (339)	795 (361)
<b>Number of Flanges</b>	8	9	8	9
<b>No. of Blades per Flange</b>	6 C-Shape			
<b>Blade Spacing</b>	7-1/2"			
<b>Max. Tilling Depth<sup>^</sup></b>	7"			
<b>Skid Shoe Settings</b>	7			
<b>Offset</b>	14"	18"	14"	18"
<b>Number of Sifting Tines</b>	N/A		43	48
<b>Rotor Swing Diameter</b>	17"			
<b>Rotor Shaft Speed</b>	220 rpm at 540 rpm PTO			
<b>PTO Driveline</b>	Category 3, Heavy Duty Shear Bolt or Slip Clutch			
<b>Gearbox</b>	50 HP, 540 rpm, Cast Iron Housing, Drain Plug			
<b>Drive Chain</b>	#80 High Tensile in Oil Bath			
<b>Sprockets</b>	Hardened Teeth, Splined Center			
<b>Colors</b>				

See page 47 for reverse-till diagram.

Quick Hitch  
SYSTEM

**5 YEAR**  
LIMITED GEARBOX  
WARRANTY

\*See dealer for complete warranty information. ^ Tilling depth depends on conditions and fluffiness of tilled area.