

# STB10/15 SERIES TRIP BLADES

HP REQUIRED  
25-70 HP

HITCH  
Universal  
Quick-Attach



SNOW TOOLS


## Efficient Snow Removal with Loader-Mount Blades.

The STB10 and STB15 Snow Trip Blades are designed to fit tractor loaders. The STB10 is available in 5' and 6' widths for tractors with loaders in the 25-40 HP range. The 10 Series Model has a 21" curved moldboard. The STB15 is designed for tractors 30 to 70 HP and is available in 6', 7', and 8' widths. The 15 Series features a 27" curved moldboard. Both models feature dual trip springs and abrasion resistant AR400 skid shoes. Hydraulic angling options are available on both units as well and both have safety orange edge markers as standard equipment.



Button-style skid shoes are manufactured from high tensile AR400 steel, and are abrasion resistant.



	STB10	STB15
<b>Horsepower Range</b>	25-40 HP	30-70 HP
<b>Hitch/Mount*</b>	Quick-Attach	Quick-Attach
<b>Widths</b>	60", 72"	72", 84", 96"
<b>Moldboard Height</b>	21" Curved Blade	27" Curved Blade
<b>Moldboard Material</b>	12 Gauge	10 Gauge
<b>Moldboard Spring Trip</b>	2 Spring Protection	
<b>Moldboard Trip</b>	Can be Locked for Light Grading	
<b>Blade Widths</b>	5-6 ft.	5-6-7-8 ft.
<b>Skid Shoes Button Style Standard</b>	AR400 Material	
<b>Angling</b>	Up to 30 Degrees	
<b>Optional Hydraulic Cylinder(s)</b>	Single, Dual or Dual with Cushion Valve	Dual or Dual with Cushion Valve
<b>Manual Angle Positions</b>	2-Left 1-Center 2-Right	
<b>Adjustable Spring Tension</b>	Standard	
<b>Carrier Lift Capacity</b>	Less than 3,500 lbs	Less than 5,000 lbs
<b>Carrier Max Operating Weight</b>	Less than 4,500 lbs	Less than 8,000 lbs
<b>Max. Hydraulic Pressure Rating</b>	3,000 psi	
<b>Replaceable Wear Edge</b>	1/2" x 6" Mild Steel or 1/2" x 6" Poly	
<b>Marker Kit</b>	Standard	
<b>Color</b>		

\*NOT to be used on Skid Steers