

TC25 TREE CARRIERS



AVAILABLE FOR: SSV65 / SSV75 / SVL65-2 / SVL75-2 / SVL95-2s

- Universal Quick-Attach plate
- Curved and tapered front edge
- Side gussets
- 1/4" AR400 bucket material
- Tie down connection points on hitch



The Tree Carrier is available in a variety of sizes to help landscapers and nurseries handle multiple widths of root balls. Easily dig, move, then plant small trees and shrubs with one versatile tool.



Curved and tapered front edge makes scoop easier to drive in the ground.

Hook points provide an easy way to secure the tree in the bucket to prevent it from falling over while transporting it.



	TC2536	TC2542	TC2548
Max. Horsepower (kW)		100 HP (74.6)	
Weight (kg)	286 lbs (130)	315 lbs (143)	345 lbs (157)
Max. Root Ball Capacity (m)	36" (.91)	42" (1.07)	48" (1.22)
Scoop Construction (mm)	Continuous welded 1/4" (6) AR400 plate steel with beveled front edge and reinforced with 5/16" (8) thick mild steel gusset plates		
Reinforced Construction (mm)	Continuous welded 5/16" (8) mild steel gussets		
Skid Resistance Step Plates (cm)	Two, 3" x 7-1/2" (8x19) bolt-on cast steel		
Hook Points	2 on each side of hitch plate		