

GB25 Series

Specifications & Capacities						
Model Numbers	GB2590	GBE2590	GB2596	GBE2596	GB25108	GBE25108
Hitch Style	Universal Quick-Attach	Euro hitch plate	Universal Quick-Attach	Euro hitch plate	Universal Quick-Attach	Euro hitch plate
Weight (Optional BOE and Valve included)	1618 lbs (734 kg)	1608 lbs (730 kg)	1658 lbs (752 kg)	1648 lbs (748 kg)	1792 lbs. (813 kg)	1786 lbs (810 kg)
Bucket Capacity (Struck)	1.00 cu yd (0.76 m ³)		1.07 cu yd (0.82 m ³)		1.18 cu yd (0.90 m ³)	
Overall Width	90" (3.29 m)		96" (2.44 m)		108" (2.74 m)	
Grapple Opening (With BOE)	84" (2.13 m)		84" (2.13 m)		84" (2.13 m)	
Number of Tines	4		4		5	
Tine Construction	Bolt-on ductile iron tine with reinforced gussets					
Tine Thickness	3/4" (19 mm)					
Hydraulic Cylinder	Dual 3" x 14" x 1 1/2" rod					
Maximum Pressure Rating	3500 psi (24132 kPa)					

39298

