

RG30 Series

Specifications & Capacities				
		RG3068	RG3074	RG3080
Weight (without shields)	lbs (kg)	931 (422.3)	947 (429.6)	1043 (473.1)
Width	in (m)	68 (1.73)	74 (1.88)	80 (2.03)
Closed Height	in (cm)	35 1/2 (90.2)		
Grapple Opening	in (m)	39 1/2 (1.00)		
Hitch Type		Universal Quick Attach		
Number of Lower Teeth		8	8	10
Hose Couplers		(1) - 1 1/16" FORB male and (1) - 1 1/16" FORB female flat faced couplers		
Number of Upper Grapple		2		
Lower Tooth Thickness		1/2 (13)		
Upper Tooth Thickness	in (mm)	3/4 (19)		
Working Length of Lower	in (cm)	31 1/2 (80)		
Upper Jaw Pivot Pins	in (cm)	Greasable 1 1/4 (3.2) pivot pins		
Hydraulic Cylinder Pivot Pins	in (cm)	Greasable 1 (2.5) pivot pins		
Hydraulic Cylinders	in (cm)	Quantity two 2 1/2 x 8 x 1 1/4 (6.4 x 20.3 x 3.2) Rod		
Maximum Pressure Rating	psi (mPa)	3500 (24.1)		
Optional Hose Shields	in (mm)	1/4 (6) Welded housing with 1/4 (6) removable cover		
Optional Cylinder Shields	in (mm)	5/16 (8) Formed channels		

